

BILGE PUMP SYSTEMS& ACCESSORIES





Bilge Pump Heavy Duty 1750 GPH 12V

Submersible heavy duty bilge pump 12V with pump capacity 110 L/min (1750 GPH) and 85 L/min (1350 GPH) at 1m head. Stainless steel shaft, double ball bearings, mechanical seal, tough thermoplastic ABS housing and a robust long-life motor design. Universal base plate with strainer and pin (for "T-slot") to attach a level switch for automatic operation. Including check valve, 32mm (1,25") and 38mm (1,5") ports. 6A fuse. For pleasure or commercial boats above 10m (30Ft) length. Interchangeable with Rule 1500, Johnson Pump 16004-00 /32-1600-01.

SKU: 01-03-011 Category: Submersible Heavy Duty

Weight (approx)	1.52 kg / 3.35 lbs
Dimensions	150/6L x 170/6.7H x 130/5W mm/in
Туре	Heavy Duty Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Pump Heavy Duty 1750 GPH 24V

Submersible heavy duty bilge pump 24V with pump capacity 110 L/min (1750 GPH) and 85 L/min (1350 GPH) at 1m head. Stainless steel shaft, double ball bearings, mechanical seal, tough thermoplastic ABS housing and a robust long-life motor design. Universal base plate with strainer and pin (for "T-slot") to attach a level switch for automatic operation. Including check valve, 32mm (1,25") and 38mm (1,5") ports. 3A fuse. For pleasure or commercial boats above 10m (30 Ft) length. Interchangeable with Rule 1500, Johnson Pump 16084-00/32-1600-02.

SKU: 01-03-012 Category: Submersible Heavy Duty

Weight (approx)	1.52 kg / 3.35 lbs
Dimensions	150/6L x 170/6.7H x 130/5W mm/in
Туре	Heavy Duty Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Pump Heavy Duty 2250 GPH 12V

Submersible heavy duty bilge pump 12V with pump capacity 140 L/min (2250 GPH) and 120 L/min (1900 GPH) at 1m head. Stainless steel shaft, double ball bearings, mechanical seal, tough thermoplastic ABS housing and a robust long-life motor design. Universal base plate with strainer and pin (for "T-slot") to attach a level switch for automatic operation. Including check valve, 32mm (1,25") and 38mm (1,5") ports. 8A fuse. For pleasure or commercial boats above 12m (36 Ft) length. Interchangeable with Rule 2000, Johnson Pump 22004/32-2200-01.

SKU: 01-03-013 Category: Submersible Heavy Duty

Weight (approx)	1.70 kg / 3.75 lbs
Dimensions	150/6L x 170/6.7H x 130/5W mm/in
Туре	Heavy Duty Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Pump Heavy Duty 2250 GPH 24V

Submersible heavy duty bilge pump 24V with pump capacity 140 L/min (2250 GPH) and 120 L/min (1900 GPH) at 1m head. Stainless steel shaft, double ball bearings, mechanical seal, tough thermoplastic ABS housing and a robust long-life motor design. Universal base plate with strainer and pin (for "T-slot") to attach a level switch for automatic operation. Including check valve, 32mm (1,25") and 38mm (1,5") ports. 4,5A fuse. For pleasure or commercial boats above 12m (36 Ft) length. Interchangeable with Rule 2000, Johnson Pump 22084/32-2200-02.

SKU: 01-03-014 Category: Submersible Heavy Duty

Weight (approx)	1.70 kg / 3.75 lbs
Dimensions	150/6L x 170/6.7H x 130/5W mm/in
Туре	Heavy Duty Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Automatic Bilge Pump 500 GPH 12V

Fully automatic bilge pump 12V, automatic activation with a built in electrical level switch. Pump capacity 32 L/min (500 GPH) and 25 L/min (400 GPH) at 1m head. Stainless steel shaft, compact and easy to install. Tough thermoplastic ABS housing and removable base plate with strainer integrated. Easy maintenance and low power consumption. A three wire design allows for automatic, manual or override mode. Including 19 mm (3/4") straight and elbow detachable discharge ports. 1,8A fuse. For pleasure boats up to 6m (20 Ft) length.

SKU: 01-04-015 Category: Submersible Automatic

	0.001 - 10.70 !!
Weight (approx)	0.32 kg / 0.70 lbs
Dimensions	151/6L x 95/3.75H x 78/3W mm/in
Туре	Automatic Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Automatic Bilge Pump 750 GPH 12V

Fully automatic bilge pump 12V, automatic activation with a built in electrical level switch. Pump capacity 50 L/min (750 GPH) and 42 L/min (660 GPH) at 1m head. Stainless steel shaft, compact and easy to install. Tough thermoplastic ABS housing and removable base plate with strainer integrated. Easy maintenance and low power consumption. A three wire design allows for automatic, manual or override mode. Including 19 mm (3/4") straight and elbow detachable discharge ports. 2,7A fuse. For pleasure boats from 6m (18 Ft) to 8m (25 Ft) length.

SKU: 01-04-016 Category: Submersible Automatic

Weight (approx)	0.45 kg / 1.0 lbs
Dimensions	151/6L x 95/3.75H x 78/3W mm/in
Туре	Automatic Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Automatic Bilge Pump 750 GPH 24V

Fully automatic bilge pump 24V, automatic activation with a built in electrical level switch. Pump capacity 50 L/min (750 GPH) and 42 L/min (660 GPH) at 1m head. Stainless steel shaft, compact and easy to install. Tough thermoplastic ABS housing and removable base plate with strainer integrated. Easy maintenance and low power consumption. A three wire design allows for automatic, manual or override mode. Including 19 mm (3/4") straight and elbow detachable discharge ports. 1,5A fuse. For pleasure boats from 6m (18 Ft) to 8m (25 Ft) length.

SKU: 01-04-017 Category: Submersible Automatic

Weight (approx)	0.45 kg / 1.0 lbs
Dimensions	151/6L x 95/3.75H x 78/3W mm/in
Туре	Automatic Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Automatic Bilge Pump 1100 GPH 12V

Fully automatic bilge pump 12V, automatic activation with a built in electrical level switch. Pump capacity 75 L/min (1100 GPH) and 65 L/min (1000 GPH) at 1m head. Stainless steel shaft, compact and easy to install. Tough thermoplastic ABS housing and removable base plate with strainer integrated. Easy maintenance and low power consumption. A three wire design allows for automatic, manual or override mode. Fixed F29 mm (1,15") straight discharge port. 4A fuse. For pleasure boats from 8m (25 Ft) to 10m (30 Ft) length.

SKU: 01-04-018 Category: Submersible Automatic

Weight (approx)	0.45 kg / 1.0 lbs
Dimensions	151/6L x 95/3.75H x 78/3W mm/in
Туре	Automatic Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Automatic Bilge Pump 1100 GPH 24V

Fully automatic bilge pump 24V, automatic activation with a built in electrical level switch. Pump capacity 75 L/min (1100 GPH) and 65 L/min (1000 GPH) at 1m head. Stainless steel shaft, compact and easy to install. Tough thermoplastic ABS housing and removable base plate with strainer integrated. Easy maintenance and low power consumption. A three wire design allows for automatic, manual or override mode. Fixed 29 mm (1,15") straight discharge port. 2,5A fuse. For pleasure boats from 8m (25 Ft) to 10m (30 Ft) length.

SKU: 01-04-019 Category: Submersible Automatic

Weight (approx)	0.45 kg / 1.0 lbs
Dimensions	151/6L x 95/3.75H x 78/3W mm/in
Туре	Automatic Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Float Switch 12/24/30V

The 12/24/30V bilge float switch activates your bilgepump automatically when water exceeds the acceptable level and deactivate when water has been removed. For a fully automatic removal of your bilge water connect a switch to your electrical bilge pump. Safe removal of bilgewater when nobody is onboard, approved for 500 000 cycles. 14A fuse.

SKU: 01-66-025 Category: Accessories

Weight (approx)	0.12 kg / 0.25 lbs
Туре	Electric Switch
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Digital Bilge Switch 12/24V

The 12/24V digital bilge switch activates your bilgepump automatically when water exceeds the acceptable level and deactivate when water has been removed. For a fully automatic removal of your bilge water connect a switch to your electrical bilge pump. Field sensing digital technology, fully sealed without any moving parts. Will not corrode and are not affected by oil or debris.

SKU: 01-66-037 Category: Accessories

Weight (approx)	0.05 kg / 0.12 lbs
Туре	Electronic Switch
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Digital Bilge Switch 12/24V-bulk

The 12/24V digital bilge switch activates your bilgepump automatically when water exceeds the acceptable level and deactivate when water has been removed. For a fully automatic removal of your bilge water connect a switch to your electrical bilge pump. Field sensing digital technology, fully sealed without any moving parts. Will not corrode and are not affected by oil or debris.

SKU: 01-39-039 Category: Accessories

Weight (approx)	0.05 kg / 0.12 lbs (per unit)
Туре	Electronic Switch
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Digital Bilge High Water Alarm Kit 12V

The 12V digital bilge sensor detects when there is water in the bilge or a tank. Field sensing digital technology, fully sealed without any moving parts. Will not corrode and are not affected by oil or debris. 12V display panel, 1 LED and piezo alarm integrated, including 152mm (6") wire leads, fuse and fuse holder.

SKU: 01-69-041 Category: Accessories

Weight (approx)	0.05 kg / 0.12 lbs
Туре	Electronic Sensor
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Digital Bilge High Water Alarm Kit 24V

The 24V digital bilge sensor detects when there is water in the bilge or a tank. Field sensing digital technology, fully sealed without any moving parts. Will not corrode and are not affected by oil or debris. 24V display panel, 1 LED and piezo alarm integrated, including 152mm (6") wire leads, fuse and fuse holder.

SKU: 01-69-042 Category: Accessories

Weight (approx)	0.12 kg / 0.25 lbs
Туре	Electronic Sensor
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Digital Bilge High Water Alarm Kit 12V-bulk

The 12V digital bilge sensor detects when there is water in the bilge or a tank. Field sensing digital technology, fully sealed without any moving parts. Will not corrode and are not affected by oil or debris. 12V display panel, 1 LED and piezo alarm integrated, including 152mm (6") wire leads, fuse and fuse holder.

SKU: 01-39-043 Category: Accessories

Weight (approx)	0.05 kg / 0.12 lbs (per unit)
Туре	Electronic Sensor
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Digital Bilge High Water Alarm Kit 24V-bulk

The 24V digital bilge sensor detects when there is water in the bilge or a tank. Field sensing digital technology, fully sealed without any moving parts. Will not corrode and are not affected by oil or debris. 24V display panel, 1 LED and piezo alarm integrated, including 152mm (6") wire leads, fuse and fuse holder.

SKU: 01-39-044 Category: Accessories

Weight (approx)	0.12 kg / 0.25 lbs (per unit)
Туре	Electronic Sensor
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Pump Panel 3-way 12V

Three- positions switch bilge pump control panel 12V. Manual, automatic or off. The automatic feature operates in combination with automatic bilge level switches or automatic bilge pumps. Integrated fuse holder, fuse and operating light.

SKU: 01-66-027 Category: Accessories

Туре	Control Panel
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Pump Panel 3-way 24V

Three- positions switch bilge pump control panel 24V. Manual, automatic or off. The automatic feature operates in combination with automatic bilge level switches or automatic bilge pumps. Integrated fuse holder, fuse and operating light.

SKU: 01-66-028 Category: Accessories

Туре	Control Panel
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Your Source For Albin Pump Marine Products & More!

CONTACT

SALES DEPARTMENT sales@bigblueoceanmarine.com
T: 1 (250) 713-1018

BIGBLUEOCEANMARINE.COM