

BILGE PUMP SYSTEMS: SUBMERSIBLE HEAVY DUTY

Made By albin.pump marine since 1928

BIGBLUEOCEANMARINE.COM



Bilge Pump Heavy Duty 1750 GPH 12V

Submersible heavy duty bilge pump 12V with pump capacity 110 L/min (1750 GPH) and 85 L/min (1350 GPH) at 1m head. Stainless steel shaft, double ball bearings, mechanical seal, tough thermoplastic ABS housing and a robust long-life motor design. Universal base plate with strainer and pin (for "T-slot") to attach a level switch for automatic operation. Including check valve, 32mm (1,25") and 38mm (1,5") ports. 6A fuse. For pleasure or commercial boats above 10m (30Ft) length. Interchangeable with Rule 1500, Johnson Pump 16004-00 /32-1600-01.

SKU: 01-03-011 Cate	gory: Submersible Heavy Duty
---------------------	------------------------------

Weight (approx)	1.52 kg / 3.35 lbs
Dimensions	150/6L x 170/6.7H x 130/5W mm/in
Туре	Heavy Duty Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Pump Heavy Duty 1750 GPH 24V

Submersible heavy duty bilge pump 24V with pump capacity 110 L/min (1750 GPH) and 85 L/min (1350 GPH) at 1m head. Stainless steel shaft, double ball bearings, mechanical seal, tough thermoplastic ABS housing and a robust long-life motor design. Universal base plate with strainer and pin (for "T-slot") to attach a level switch for automatic operation. Including check valve, 32mm (1,25") and 38mm (1,5") ports. 3A fuse. For pleasure or commercial boats above 10m (30 Ft) length. Interchangeable with Rule 1500, Johnson Pump 16084-00/32-1600-02.

SKU: 01-03-012 Category: Submersible Heavy Duty

Weight (approx)	1.52 kg / 3.35 lbs
Dimensions	150/6L x 170/6.7H x 130/5W mm/in
Туре	Heavy Duty Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Pump Heavy Duty 2250 GPH 12V

Submersible heavy duty bilge pump 12V with pump capacity 140 L/min (2250 GPH) and 120 L/min (1900 GPH) at 1m head. Stainless steel shaft, double ball bearings, mechanical seal, tough thermoplastic ABS housing and a robust long-life motor design. Universal base plate with strainer and pin (for "T-slot") to attach a level switch for automatic operation. Including check valve, 32mm (1,25") and 38mm (1,5") ports. 8A fuse. For pleasure or commercial boats above 12m (36 Ft) length. Interchangeable with Rule 2000, Johnson Pump 22004/32-2200-01.

SKU: 01-03-013 Category: Submersible Heavy Duty

Weight (approx)	1.70 kg / 3.75 lbs
Dimensions	150/6L x 170/6.7H x 130/5W mm/in
Туре	Heavy Duty Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Bilge Pump Heavy Duty 2250 GPH 24V

Submersible heavy duty bilge pump 24V with pump capacity 140 L/min (2250 GPH) and 120 L/min (1900 GPH) at 1m head. Stainless steel shaft, double ball bearings, mechanical seal, tough thermoplastic ABS housing and a robust long-life motor design. Universal base plate with strainer and pin (for "T-slot") to attach a level switch for automatic operation. Including check valve, 32mm (1,25") and 38mm (1,5") ports. 4,5A fuse. For pleasure or commercial boats above 12m (36 Ft) length. Interchangeable with Rule 2000, Johnson Pump 22084/32-2200-02.

SKU: 01-03-014 Ca	ategory: Submersible Heavy Duty
Weight (approx)	1.70 kg / 3.75 lbs
Dimensions	150/6L x 170/6.7H x 130/5W mm/in
Туре	Heavy Duty Submersible
Certification	CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance





Your Source For Albin Pump Marine Products & More!

CONTACT

SALES DEPARTMENT sales@bigblueoceanmarine.com T: 1 (250) 713-1018

BIGBLUEOCEANMARINE.COM