

MACERATOR

FEATURES	BENEFITS	COMPETITIVE ADVANTAGES
Bronze chopping blade	No rust rotary cutter	Rotary cutter corrosion-free
Easy mount bracket	Easy installation	Easy installation with any position mount capability
Johnson Pump quality impeller	Long impeller life	Short run dry periods without damage - Less Maintenance
ISO 8846 ignition protected motor	Protected against ignition of flammable gases	
Thermoplastic polyester rotary cutter casing		



TA3P10-19
Macerator Pump

TECHNICAL SPECIFICATIONS

PART NUMBER	DESCRIPTION	CAPACITY AT 0.2 BAR (6.7 FT)	INLET CONNECTION	AMPERAGE	FUSE SIZE	OUTLET CONNECTION
10-24453-01	TA3P10-19 12V Macerator	10 GPM (37 l/min)	1 1/2" (Ø 38 mm) hose or 1 1/2" NPT	15 A	20 A	1" (25.4 mm) hose
10-24453-02	TA3P10-19 24V Macerator	10 GPM (37 l/min)	1 1/2" (Ø 38 mm) hose or 1 1/2" NPT	7 A	12 A	1" (25.4 mm) hose

GENERAL INFORMATION

MOTOR	12/24V DC (with build-in thermal protection)
BODY	Phenol plastic (PF)
IMPELLER	Nitrile 09-1052S-9
HOUSING	Thermoplastic polyester (PET)
SHAFT	Stainless steel
SEAL	Lip seal



TA3P10-19
Macerator Pump

Dimensions

HEIGHT	LENGTH	WIDTH	WEIGHT
3.23" (82 mm)	9.06" (230 mm)	4.25" (108 mm)	4.2 lbs (1.9 kg)

Spare Parts

PART NUMBER	DESCRIPTION
09-45595	Rebuild Kit

SPXFLOW®

SPX FLOW, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. The green "X" is a trademark of SPX FLOW, Inc.

For more information, visit www.spxflow.com/johnson-pump-marine